

Middling capacity magnetizer

Typical model

KCJ-3030GP1S /2S, KCJ-3040GP1S /2S, KCJ-3060GP1S /2S

Peculiarity

- Adopt PLC control, constant current charging.
- According you need, can choose single line output type (P1S) or dual output type (P2S).
- Output Voltage number and finger table show together, the voltage range in 50V to 3000V can move freely.
- Capacitance can switch and show.
- Function of take count of turnout.
- Function of show the pulse current.
- Can increase demagnetization function. (/ T)

Fit range

- ◆ For high coercive force NbFeb magnet material.
- ◆ For middle and mini-size SmCo magnet material.
- ◆ For large size of NbFeB and ferrite magnet material loudspeaker.



Model	KCJ-3030GP1S	KCJ-3040GP1S	KCJ-3060GP1S
Power	AC.220V 30A	AC.220V 40A	AC.220V 40A
Output Volt	DC 50V~3000V	DC 50V~3000V	DC 50V~3000V
Max. output curr	40,000A	40,000A	40,000A
Capacitance	3000 uF	4000 uF	6000 uF
Discharge energy	13500 J	18000 J	27000 J
Charge time	About 8s (MAX)	About 9s (MAX)	About 12s (MAX)
Output load	Multi-poles or Coil	Multi-poles or Coil	Multi-poles or Coil
Dimensions	W D H 850x1100x1570	W D H 850x1100x1570	W D H 850x1520x1600
Weight	About 470KG	About 520KG	About 750KG

充磁、退磁、测量磁

我们能

Magnetizing, Demagnetizing, Magnetic measurements, All we can