

## Special for permanent magnet DC motor magnetizer

### Typical model

KCJ-3005GP1S、KCJ-1510GP1S、KCJ-1520GP1S、KCJ-1540GP1S

### Peculiarity

- Adopt high voltage pulse Capacitance and PLC Control technology .
- Output Voltage number and finger table show together, the voltage range is 50V to3000V (50V~1500V) can be moved freely.
- Capacitance can be switched and show.
- Can show output pulse current .
- Function of take count of turnout.



### Fit range

- ◆ Radial magnetizing for small type NdFeB motor, bonded NdFeB motor and Ferrite motor.

Model	KCJ-3005GP1S	KCJ-1520GP1S	KCJ-1540GP1S
Power	AC.220V 20A	AC.220V 20A	AC.220V 20A
Output Volt	DC 50V~3000V	DC 50V~1500V	DC 50V~1500V
Max. output curr	20,000A	20,000A	20,000A
Capacitance	500 uF	2000 uF	4000 uF
Discharge energy	2250 J	2250 J	4500 J
Charge time	About 3s (MAX)	About 5s (MAX)	About 6s (MAX)
Output load	Multi-poles or Coil	Multi-poles or Coil	Multi-poles or Coil
Dimensions	W D H 550x770x1270	W D H 550x770x1270	W D H 550x770x1270
Weight	About 200KG	About 220KG	About 235KG

充磁、退磁、测量磁

**我们能**

Magnetizing, Demagnetizing, Magnetic measurements, All we can