

C series magnetizer

Typical model

KCJ-C80、KCJ-C120、KCJ-C160、KCJ-C240

Peculiarity

- Adopt high voltage pulse Capacitance .
- Output Voltage number and finger table show together, the voltage range in 50V to 1200V can move freely.
- Capacitance can switch and show.
- Function of take count of turnout.
- Low inductance load model (suffix G) .
- Can increase demagnetization function. (/ T)

Fit range

- ◆ For NbFeB, Ferrite and SmCo's magnet material.
- ◆ Overall magnetizing for permanent magnet DC motor.
- ◆ For NbFeb and Ferrite's loudspeakers.
- ◆ For large size magnet material.



Modelle	KCJ-C80	KCJ-C120	KCJ-C160	KCJ-C240
Power	AC.220V 15A	AC.220V 15A	AC.220V 25A	AC.220V 30A
Output Volt	DC 50V~1200V	DC 50V~1200V	DC 50V~1200V	DC 50V~1200V
Max. output curr	20,000A	20,000A	20,000A	20,000A
Capacitance	8000 uF	12000 uF	16000 uF	24000 uF
Discharge energy	5760 J	8640 J	11520 J	17280J
Charge time	About 7s (MAX)	About 9s (MAX)	About 11s (MAX)	About 15s (MAX)
Output load	Coil	Coil	Coil	Coil
Dimensions	W D H 700x900x1350	W D H 700x900x1350	W D H 700x900x1350	W D H 850x1100x1570
Weight	About 210KG	About 235KG	About 290KG	About 480KG

充磁、退磁、测量磁

我们能

Magnetizing, Demagnetizing, Magnetic measurements, All we can